

Liquid Gas Membrane Primer

Page 1



nbsPlus

Description

Visqueen Liquid Gas Membrane Primer is part of Visqueen's liquid membrane system and used to prepare surfaces before the application of the main liquid membrane.

Visqueen Liquid Gas Membrane Primer is supplied in 5L drums and only requires agitation prior to use. Visqueen Liquid Gas Membrane Primer can be applied by brush, roller or airless spray.

Installation

For optimum performance, all substrates should be primed with Visqueen Liquid Gas Membrane Primer at a rate of 0.25 litre/m². Ensure that the primer is applied evenly and if spraying, use a circular action. Allow the primer to dry (approximately 2 hours depending upon surface, temperature, humidity and ventilation).

For recommended dilution rates please consult with our Visqueen technical team (0845 302 4758) as these can vary depending on the application.

Shelf life and Storage

Visqueen Liquid Gas Membrane Primer has a minimum shelf life of 12 months when stored in sealed containers at temperatures of 5°C to 25°C. The product must not be subjected to temperatures below 5°C during storage or transportation.

Temperatures below 5°C will render the product unfit for use. Store in a dry location out of direct sunlight.

Health and Safety

Visqueen Liquid Gas Membrane Primer's Health and Safety datasheet is available on our website or on request and should be read prior to product use.

VISQUEEN
BUILDING PRODUCTS



Liquid Gas Membrane Primer

Appendix A



Visqueen Building Products

Visqueen is the market leader in the manufacture and supply of structural waterproofing and gas protection systems. Visqueen offers the complete package - a proven, reliable range backed by a technical support service that goes unmatched in the market - everything you would expect from a reputable and ethical company.

System Accessories

To ensure full waterproofing protection please use the following certified system components:

- Visqueen High Performance (HP) Tanking Primer
- Visqueen TreadGUARD1500
- Visqueen Protect&Drain
- Visqueen Top Hat Unit

Downloads Library

- Technical Datasheet
- Declaration of Performance
- Visqueen's Guide to CE Marking

Find your local stockist

Search our directory of Visqueen specification Stocking Centres to locate your nearest Visqueen Partner.

Distributor Support

Our specification Stocking Centres can access a free library of sales support tools, bespoke catalogues and more, [click here](#).

Technical support throughout your project

We are specialists in our field and can help you specify the correct solutions with the necessary performance levels, in accordance with building regulations.

- Nationwide site support team
- Specification advice
- Installation guidance & project sign off
- System design including CAD details

