

Visqueen GX Retaining Discs

Page 1



nbsPlus

- Secures Pre Applied Membrane to vertical applications
- Suitable for formwork or adjoining structure

Description

A plastic disc 50mm x 35mm head supplied in boxes of 500

Application

Visqueen GX Retaining Discs secures Pre Applied Membrane to vertical applications such as formwork or adjoining structures

Installation

Visqueen Retaining Discs are available to provide a means for securing the leading edge of the membrane to shuttering. The membrane should be installed with the textured surface facing away from the shuttering.

Using oval nails, Visqueen Retaining Discs should be mechanically fixed, at maximum 400mm centres, to the internal face of the shuttering. Using a suitable power tool and 6mm drill bit to create a pilot hole in the membrane, the Visqueen Pre Applied Membrane should be secured over the protruding section of the retaining disc. The top edge of the membrane should be trimmed to

approximately 20mm below the top edge of the slab. Once the concrete has set, the oval nails should be removed by pulling through from the external face of the shuttering. When the shuttering is removed the Visqueen Retaining Discs should be visible on the external (smooth) face of the membrane. Continuity of the membrane system with the damp or gas proof course is maintained using Visqueen GR Self Adhesive Membrane (see Visqueen Typical Details).

Technical

Dimensions – 50mm x 35mm

Packaging – 500 per box

Storage

Store in a warm – above 5oC – and dry environment.

VISQUEEN
 BUILDING PRODUCTS



Visqueen GX Retaining Discs

Appendix A



Visqueen Building Products

Visqueen is the market leader in the manufacture and supply of structural waterproofing and gas protection systems. Visqueen offers the complete package - a proven, reliable range backed by a technical support service that goes unmatched in the market - everything you would expect from a reputable and ethical company.

System Accessories

To ensure full waterproofing protection please use the following certified system components:

- Visqueen High Performance (HP) Tanking Primer
- Visqueen TreadGUARD1500
- Visqueen Protect&Drain
- Visqueen Top Hat Unit

Downloads Library

- Technical Datasheet
- Declaration of Performance
- Visqueen's Guide to CE Marking

Find your local stockist

Search our directory of Visqueen specification Stocking Centres to locate your nearest Visqueen Partner.

Distributor Support

Our specification Stocking Centres can access a free library of sales support tools, bespoke catalogues and more, [click here](#).

Technical support throughout your project

We are specialists in our field and can help you specify the correct solutions with the necessary performance levels, in accordance with building regulations.

- Nationwide site support team
- Specification advice
- Installation guidance & project sign off
- System design including CAD details

