

Declaration of Performance
VBP/CPR/DPC002



Visqueen Building Products
Heanor Gate Industrial Estate
Heanor, Derbyshire UK
DE75 7RG

Declares that the products stated below conform to:

Annex ZA of EN 14909: Flexible sheets for waterproofing

Products

Visqueen GX Hydrocarbon Damp Proof Course (GR DPC)

Product Type

Type A in accordance to EN 14909

System of assessment of verification of constancy of performance (AVCP)

System 3

Use

The purpose of the damp proof course is to prevent water rising up a wall from the ground, water moving from one part of the wall to another and to deflect water from an inner wall of a cavity wall construction to the exterior of the building. They may also be used in masonry chimneys and parapet walls to protect the inside of the building from water moving.

Compliance

Visqueen DPC products are manufactured under a Quality Management System (ISO 9001) - Certificate of Compliance reference no. 4560-3 by Knight International applies.

British Research Establishment Ltd Bucknalls Lane, Watford WD25 9XX performed all Initial Type Testing (ITT).

Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	F	EN 14909
Water tightness	Pass	
Resistance to Impact	600mm	
Resistance to low temperature flexibility	-40°C	
Durability against heat ageing	Pass	
Durability against alkali	Pass	

Place

Signature

Date

Derbyshire, UK

17/05/2013

Cameron Yates
Product Manager