

FLOOR PROTECTION

VISQUEEN

MEGAFILM
FLOOR PROTECTION

www.visqueenmegafilm.co.uk

COMPLETE FLAME RETARDANT FLOOR PROTECTION



Approved to LPS1207
Cert. no. 521a/01

- COMPREHENSIVE RANGE OF GRADES TO SUIT MOST FLOOR APPLICATIONS AND SURFACES.
- UNIQUE MOULDED AND EMBOSSED SHEETING OFFERING ENHANCED PROTECTION AND SAFETY.
- ANTI-SLIP AND HIGH IMPACT CHARACTERISTICS ACROSS ALL RANGES.
- CUSTOM PRINTING AVAILABLE FOR PROJECTION OF CORPORATE IMAGE.

DESCRIPTION

Visqueen Megafilm® Flame Retardant range has accreditation to LPS 1207. LPS 1207 is the performance standard for protective materials that are used internally whilst buildings undergo refurbishment or construction.

The unique pyramid structure allows air flow whilst Visqueen Megafilm High Performance offers both additional anti-slip and impact cushioning benefits.

It is durable, tear resistant and contains dirt and any spillages. Visqueen Megafilm® is easy to tailor fit as it only needs to be cut into shape.

APPLICATION

Visqueen Megafilm® Floor Protection Systems are a range of embossed and moulded plastic sheeting designed to suit a variety of floor applications; to ease specification we have created a Product Selector.



For further information and full datasheet on each of our products please visit
www.visqueenmegafilm.co.uk

The use of non-certificated LPS 1207 materials could result in the withdrawal of insurance cover in the event of fire.



PRODUCT APPLICATION SELECTOR

LIGHT GRADE CARPET PROTECTION

Product Code	Thickness	Roll Size	Application	Flame Retardant
E1	65µm	1.5m x 167m	Dust Covering	✓
E2	120µm	1.5m x 134m	Light Carpet Protection	✓

HIGH PERFORMANCE CARPET PROTECTION

HLS	120µm	1.82m x 55m	Light Duty Carpet Protection	✓
6LS-FR	175µm	1.82m x 55m	Medium Duty Carpet Protection	✓
10LS-FR	300µm	1.82m x 55m	Heavy Duty Carpet Protection	✓

HARD FLOOR PROTECTION

3SF	175µm	1.82m x 55m	Medium Duty Hard Floor Protection	✓
4SF	300µm	1.82m x 55m	Heavy Duty Hard Floor Protection	✓

VISQUEEN MEGAFILM® PROTECTION SYSTEM

Table 1: Product tests in compliance with loss prevention standard LPS 1207

Property	Test
Ignitability by Direct Flame Impingement	BS 476: Part 12:1991 Source C, 20 seconds
Smoke Emissions Test	EN 2825
Toxic Gas Emission Test	EN 2826
Critical Oxygen Index	BS 2782: Part 1: Method 141: 1986 (ISO 4589)

VISQUEEN JOINTING TAPES

Dimensional Data	
Medium Duty Tape: 77mm x 66m	Suitable for carpets
T600 Tape: 50mm x 50m	Suitable for most surfaces except carpets



Approved to LPS1207
 Cert. no. 521a/01

VISQUEEN MEGABOARD PROTECTION

DESCRIPTION

Visqueen Megaboard® is a lightweight corrugated twin wall plastic board accredited to LPS 1207. Visqueen Megaboard® offers protection for vertical applications such as walls, pillars, columns and doors and protects ceramic, timber, marble and tiled application.

INSTALLATION

Visqueen Megaboard® is easy to handle and can be cut, scored or bent to suit any application's requirements. Visqueen Megaboard® can simply be cut to shape and size, scored or bent to fit corners and held in place using Visqueen Jointing Tapes.

STORAGE & HANDLING

Visqueen Megaboard® is available in sheet format and requires careful handling and storage to avoid damage during installation, it is recommended that Visqueen Megaboard® be stored flat.



Approved to LPS1207
Cert. no.688/01



Product Code	Thickness	Board Size	Application	Flame Retardant
Megaboard	2mm	2.44m x 1.22m x 2mm	Vertical Applications – walls pillars and columns	✓

VISQUEEN MEGATAC FLOOR PROTECTION

DESCRIPTION

Visqueen Megatac is a self adhesive film used during refurbishment and redecoration available as standard or flame retardant. Visqueen Megatac provides a tight bond with the surface which is easy to remove and leaves behind no residue.



APPLICATION

- Suitable only for use on carpets.
- Ideal for stairways, hallways and room perimeters. Can also be used as a temporary internal walkway.
- Visqueen Megatac is for temporary use only and must be removed within 45 days.

Do not apply to wet or damp carpets. Allow 72 hours before applying to newly laid carpets.

INSTALLATION

- Peel back the edge of the protective film and unroll it slightly. Press the edge onto the surface of the carpet so that it adheres firmly.
- Continue to unroll the film applying pressure and smoothing the film across the surface.
- Once the desired length has been achieved, carefully cut the end with a knife or box cutter.
- To make it easy to find the edge of the roll ready for the next length of film, fold the edge back against the roll.

Product Code	Thickness	Roll Size	Application	Flame Retardant
Megatac Trade	75µm	600mm x 100m	Self Adhesive Carpet Protection	✓
Megatac FR	75µm	900mm x 100m	Self Adhesive Carpet Protection	✓

For further information and full datasheet on each of our products please visit www.visqueenmegafilm.co.uk